



# Revolutionizing the Drive-Thru

*It's about time.*

## DURA-GLIDE® DT™ DRIVE-THRU DOOR/WINDOW

**Improve throughput and customer experience with our automatic drive-thru door/window.**

Developed alongside global QSR leaders, the Dura-Glide® DT™ is designed specifically to help restaurants face their greatest challenges at the drive-thru. With the flexibility to operate in window or door mode, staff can easily service drive-thru customers as well as parked cars or 3rd party delivery services. This flexibility facilitates a quicker exchange, minimizes steps and reduces wait times.

### Features and Benefits

- Hands-free automation allows employees to effortlessly serve customers, even with hands full
- Wide CDO width to accommodate large orders
- Built tough to stand up to the demands and constant use in food service environments
- Beautiful, sleek aesthetic
- Minimal gaps and easy to clean materials
- Solenoid locks secure panels to prevent unauthorized entry
- Powered by the Dura-Glide® header and drive system



We've taken our most trusted automatic door, the Dura-Glide®, and reimagined it for the specific, evolving needs of the drive-thru. Dual-mode operation allows for the most flexibility to serve customers quickly and efficiently.



## DOOR MODE

- Door mode is ideal for times of high drive-thru traffic volume.
- Fully automatic doors allow staff to easily serve larger orders or run orders out to parked cars.
- 32" clear door opening. Custom sizes available.
- Re-entry through access control such as keypad or card reader.

## WINDOW MODE

- Wide, fully automatic window allows staff to easily serve orders to drive-thru customers.
- 32" clear door opening. Custom sizes available.



**LEARN MORE**

- Intuitive design allows for safe and easy operation.
- Staff can easily switch between door and window mode with one-handed operation.
- Various activation options available, including hands-free activation or floor mat activation.

## SPECIFICATIONS

Description	Configuration
Design	Based on Dura-Glide 2000/3000 architecture and drive train, which has been commercially successful for over 30 years.
Finish	Clear or Dark Bronze Anodized   OPTION: Special Finishes Available
Typical Package Height	7'-8" (2.3m), Clear Door Opening of 6'-11" (2.1m) OPTION: Taller options available*
Typical Width (Narrow Stiles)	84" (CDO width 32")   Other Widths Available
Header Size	8" (203mm) High x 6" (152mm) Deep
Jamb Dimension	1 3/4" x 6"
Stiles	Narrow 2"
Typical Door Panel Weight	Up to 220 Pounds Each (100kg)
Power Required	120 VAC, 50/60 HZ, 5 Amps Minimum
Drive System	1/4 HP DC Motor, Gear Drive, Toothed belt
Controls	4 Position Rotary Switch
Controller	High Resolution iQ Controller, Microprocessor Based, Safety Logic
Activation/Safety Sensors	Push Plate (hard wired) Doorway Holding Beams for added safety OPTIONS: Mats, Wireless Wall Plates, Touchless Activation Sensor (hard wired or wireless) Card Readers, Floor Pressure Mat Switch
Locking	Key/thumb turn hook bolt   OPTION: Lock Position Indicators, Electric Solenoid Lock (Fail Safe/Fail Secure)
Security Options	Alarm contacts for remote monitoring of panel status
Temperature Rating	-30F to 130F
Glass Stops	1/4"   OPTION: 1/2", 5/8", 1"
Speed Range	Closing Speeds: 0.5 - 1.5 feet per second per ANSI. Opening Speeds: 0.5 - 2.5 feet per sec.
Codes & Standards	UL, cUL, ANSI/BHMA A156.10

## OPTIONAL FEATURES

- Glass or Infilled Panels
- Threshold Options to Interface with Various Flooring
- Transom Options
- Special Finishes Available